



GAS TEST PRESSURE GAUGE 2" 3/4" FNPT

Utility Gauge For Wide Range of Applications

CARBO Instruments Datasheet D20-PG 02.2020

Product Features & Applications

- ASME B40.1 Grade B Accuracy Compliance
- Black Steel Case
- Brass Vent Valve
- Reliable and Economical
- Applications: Oil, Water, Air, Compressor, Hydraulics, HVAC, Gaseous & Liquid media that are not highly viscous or crystallizing and not corrosive or oxidizing to copper alloy parts and Steel.

Specifications

Accuracy

ASME B40.1 Grade B Accuracy $\pm 3-2-3$ % of span

Dial Size

2" (50 mm)

Connection

3/4" FNPT

Scale

Dual Scale: psi / with kPa

Material

Movement: Copper Alloy
 Bourdon Tube: Copper Alloy
 Connection: Copper Alloy
 Window: Glass Lens
 Casing: Steel Case
 Body Assembly: Steel
 Pointer: Aluminum

Permissible Ambient Temperature:

-4°F to 140°F (-20°C to 60°C)

Fill: Dry

Manufactured in an **ISO 9001 Certified** factory to meet and exceed your expectation

Options: - Custom Dial Layout - Anti Vibration - see L20 Series
 - Special Connection Size - Adapters & Mounting kit



Range / Scale	Part Number
15 psi	D20-PG-015
30 psi	D20-PG-030
60 psi	D20-PG-060

Specifications subject to change without notice at any time, and information provided may vary from the actual Product.

CARBO USA LLC
 1541 Prudential Dr
 Dallas, TX 75235
 Tel: (972) 803-4040
 info@carbousa.com

carbousa.com

Warning: This product contains chemicals such as lead in brass component known to the state of California to cause cancer and birth defects or other reproductive harms.