



WATER TEST PRESSURE GAUGE 2-1/2" 3/4" Female Hose Thread

Utility Gauge For Wide Range of Applications

CARBO Instruments Datasheet D25-P-W 02.2019

Product Features & Applications

- ASME B40.1 Grade B Accuracy Compliance
- Strong Case - Durable
- Large Dial Print
- Reliable and Economical
- Applications: Oil, Water, Air, Compressor, Hydraulics, HVAC, Gaseous & Liquid media that are not highly viscous or crystallizing and not corrosive or oxidizing to copper alloy parts.

Specifications

Accuracy

ASME B40.1 Grade B Accuracy $\pm 3-2-3$ % of span

Dial Size

2 1/2" (63 mm)

Connection

3/4" Female Hose Thread

Scale

Dual Scale: psi / bar with kPa guidance

Case Design

Red Pointer with Brass Nob

Material

Movement: Copper Alloy
Bourdon Tube: Copper Alloy
Connection: Copper Alloy
Window: Plastic Lens
Casing: Plastic Case
Pointer: Aluminum

Permissible Ambient Temperature:
-4°F to 140°F (-20°C to 60°C)

Fill: Dry

Manufactured in an **ISO 9001 Certified** factory to meet and exceed your expectation



Range / Scale	Part Number
15 psi	D25-P-W-015
30 psi	D25-P-W-030
60 psi	D25-P-W-060
100 psi	D25-P-W-100
160 psi	D25-P-W-160
200 psi	D25-P-W-200
300 psi	D25-P-W-300
400 psi	D25-P-W-400
600 psi	D25-P-W-600

Options: - Custom Dial Layout - Anti Vibration - see L25 Series
 - Special Connection Size - Adapters & Mounting kit

Specifications subject to change without notice at any time, and information provided may vary from the actual Product.

CARBO USA LLC
1541 Prudential Dr
Dallas, TX 75235
Tel: (972) 803-4040
info@carbousa.com

carbousa.com

Warning: This product contains chemicals such as lead in brass component known to the state of California to cause cancer and birth defects or other reproductive harms.